



NOTE* When ordering, refer to WYE STANDARDS sheet

Wye - WYE

CONNECTIONS*			REFER TO LEGEND			
STANDARD*			USE FOR NON-STANDARD FLANGES ONLY			

FITTING #	A ϕ	B ϕ	C ϕ	D	X	Y	STANDARD*			USE FOR NON-STANDARD FLANGES ONLY				REMARKS	
							"A"	"B"	"C"	SPEC	I.D.	O.D.	B.C.		HOLE SIZE
										"A"					
										"B"					
										"C"					
										"A"					
										"B"					
										"C"					
										"A"					
										"B"					
										"C"					

Pressure Class in w.g.	+	-	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
------------------------	---	---	---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----

Company Name: _____
 Contact Name: _____ Phone#: _____
 Project Name: _____ Date: _____
 Project #: _____ GDS Project #: _____

CONNECTION LEGEND	
TYPE	MATERIAL
KF = NW-ISO-KF	BI = BLACK IRON
FB = FLAT BAR	304 = STAINLESS
AR = ANGLE RING	SPEC = FB 304 S.S. ONLY
RAW = NO FLANGE	

STANDARD ELBOWS SHALL HAVE A MINIMUM CENTELINE RADIUS 1-1/2 TIMES THE DUCT DIAMETER WHENEVER POSSIBLE. HALF-RADIUS ELBOWS AVAILABLE UPON REQUEST.